

1. Make sure the printer power is on.
2. Open the print cartridge access door.
3. Remove the print cartridge from its packaging.

Hold the print cartridge by the blue, red or black surfaces only.
Do not touch the copper area.

4. Carefully remove the tape covering the printhead.
Be sure to remove all the tape. Do not touch the copper area.

5. Insert the print cartridge in the carrier.

The cartridges must be inserted in the correct position in the print cartridge carrier. A colored bar appears above each position. The colors match the colored tops of the print cartridges. The black cartridge is installed in the left position and color cartridge is installed in the right position.

6. Push the cartridge back until it clicks into place.

If the print cartridge moves loosely in the carrier, it is not locked into place. Repeat this step.

7. Install the second cartridge using the same steps.

Both print cartridges should now be installed.

8. Close the print cartridge access door.

9. Continue following the instructions on your computer screen.

10. Align the printheads.

The Align Cartridges dialog box appears on your screen and the printer prints a test page with horizontal patterns and vertical patterns. Each pattern has a number located beneath it. An example follows:


Horizontal Alignment of Heads



Vertical Alignment of Heads



Bidirectional Alignment Pattern (Black)



Bidirectional Alignment Pattern (Color)





11. Using the printed test page, select the number of the patterns that are aligned correctly.

In our example, 3 is the correct choice for Horizontal Alignment, 4 is the correct choice for Vertical Alignment, and 3 is the correct choice for the bidirectional alignment black and color.

12. Enter the number located under each pattern into the boxes on the Align Cartridges dialog box.

13. Choose OK.

14. Choose Close when cartridge installation is complete.

NOTE: Do not remove the print cartridges because they will dry out. Remove them only when you are instructed to do so, or when you are replacing them.

(BKL/all-02/15/96)